

CX2510

Main Features

- **Engine Gross Power:** 24.5 hp (18.2 kW)
- **PTO Type:** Transmission
- **Transmission Type:** Manual
- **Shuttle:** Dry Single
- Tilt Wheel with Power Steering
- Illuminated Dashboard
- Comfortable Seat with Suspension
- Single Lever Joystick
- USB and Power Socket
- Rear PTO with adjustable three-point hitch
- High Capacity Hydraulic Pump

This post is also available in: [FR](#)

Tilt Wheel with Power Steering

Hydrostatic power steering minimizes the effort required to make tight, repetitive turns. The standard tilt steering wheel ensures all operators have a comfortable driving experience.

Comfortable Seat with Suspension

With a high-quality adjustable suspension seat, the operator enjoys a comfortable and smooth ride. A seat belt is included for safety.

USB and Power Socket

Power and USB sockets come standard to meet a variety of electrical needs.

Hi/Low Speed Ranges

The CX2510 features a Hi/Low range transmission to maximize performance and efficiency.

Engine

Engine Model	3A165LWH-U
Engine Gross Power	24.5 hp (18.2 kW)
Rated Speed	2,600 rpm
No. of Cylinders	3
Fuel Type	Diesel
Aspiration	Natural
Displacement	87 cu. in (1,647 cc)
Fuel Tank Capacity	6.6 gal. (25L)

Transmission

Transmission Type	6X2 Manual Transmission
Main Gear	Manual
No. Travel Speeds	6F/2R
Min. Travel Speed	0.75 mph (1.22 km/h)

Illuminated Dashboard

The dashboard illuminates when the engine is started ensuring great visibility while working in bright daylight or at night.

Single Lever Joystick

The operation of the front loader is made easier by the use of a single lever joystick. The lever automatically returns to neutral and the loader stops in place when the joystick is released. A float position allows the bucket free floatation over the ground surface.

Rear PTO and 3-Point Hitch

Rear PTO is standard and mid-PTO is optional. You can select the rear or mid-PTO separately or simultaneously. With an adjustable right side lift rod and top link, you can easily and quickly attach implements.

Foldable ROPS

The standard fold-down roll bar makes it quick and easy to maneuver in low clearance areas.

Max. Travel Speed

10.8 mph (19.07 km/h)

Power Take-Off (PTO)

PTO Type Transmission	Manual
PTO Power	19.3 hp (14.4 kW)
Rear PTO Speeds	540 rpm
Mid PTO Speeds	2,000 rpm (Optional)

Brakes and Clutch

Brakes	Wet Disc Type
Clutch	Dry Single Stage

Dimensions w/ Ag Tire

Length w/ 3-point	109.08 in. (2,790 mm)
Width	49.4 in. (1,256 mm)
Height from Top of ROPS	82.8 in. (2,103 mm)
Wheelbase	59.8 in. (1,520 mm)
Ground Clearance	13.4 in. (340 mm)
Front Tread Ag Tires - Min	38.1 in. (968 mm)
Rear Tread Ag Tires - Min	37.4 in. (951 mm)
Min. Turning Radius w/Brake	8.3 ft. (2.53 m)

Hydraulics

Total Pump Flow	11.3 gpm (42.9 L/min)
-----------------	-----------------------

3-Point Hitch

Standard Category	Category 1
Lift Capacity, 24" aft of hitch	1,203 lbs (546 kg)
Control Type	Position

Weight

Weight w/ Ag Tires w/ROPS	2,260 lbs. (1,025 kg)
---------------------------	-----------------------

Equipment & Panel

Standard Equipment

- Hydrostatic Power Steering
- Rear PTO
- Headlights
- Safety Lights
- Cup Holder
- Illuminated Dashboard
- Wet Multi Disc Brakes
- Joystick Valve
- Adjustable Seat
- Parking Brake
- Adjustable Seat with LH/RH Armrest
- Toolbox
- USB/12 Volt Power Source

Optional Equipment

- Single Remote Hydraulic Valve
- Rear Working Light
- Front Weight
- 7 Pin Socket
- Mid PTO
- 3rd Function Kit
- Sun Canopy
- Clevis Type Drawbar
- Telescopic Three Point Lift Arms
- Engine Block Heater
- Beacon Lamp Wire Kit
- Dual Air Filter
- HST Linked Pedal

Instrument Panel

- Digital Hour Meter
- Coolant Temperature Gauge
- Electrical Tachometer
- Fuel Gauge
- Engine Oil Pressure Light
- High Beam, Emergency Flasher, Direction Indicators
- Glow Plug Light
- Alternator Light

Available Tires


Agriculture

 Front 7.0-12
 Rear 11.2-16

**Turf**

Front 23X8.5-12
Rear 33X12.5-16.5

**Industrial**

Front 23X8.5-12
Rear 12-16.5

Attachments

Front End Loaders : KL2510



Fits the CK2510. The KIOTI KL2510 front end loader is specifically designed for the CK2510 tractors, providing efficient performance with single lever joystick control. The KIOTI loader, with a built-in parking stand, is designed to be quickly and easily attached and detached. KL Series loaders utilize the tractor's hydraulic system, feature single-lever control with float and come with a bucket level indicator. *Specifications may vary with tractor model, front axle configurations, tire size option and type of attachment and are subject to change without notification.

Backhoes : KB2465



Fits KIOTI CK2510 & CK2510H tractors. Specifications may vary depending on tractor model and are subject to change without notification. Tractors must be equipped with ROPS and seat belt that will provide greater safety.

Implements

Products : Implements



Mowing, cutting, tilling, haying, hauling. Whatever the job is, KIOTI has user-friendly, high performance implements to help you get it done.